



SATA III M.2 2280 SSD

Datasheet

Product interface

M.2 2280

capacity

256GB/512GB/1TB/2TB

power dissipation

operating power consumption: 2.0W (maximum typical value)

Static power consumption: 1.0W (maximum typical value)

Dimension specifications (length*width, height/mm)

M.2 2280

(80±0.15) x (22±0.15)mm, ≤2.15mm

reliability

Mean Time Between Failures (MTBF): 1.5 million hours

vibration compatibility

Non-working mode:3.13 Grms (5Hz ~800Hz)

Shock resistance

Non-working: 1500G,0.5ms, 3 axes

function

1 MB sequential read speed: up to 550 MB/s (maximum typical value)

1 MB sequential write speed: up to 510 MB/s (maximum typical value)

4 K random read: up to 55K I/O operations per second (maximum typical value)

4 K random write: Maximum 47K I/O operations (maximum typical value)

Temperature

working range: 0°C to +70°C

storage: -40°C to +85°C

Interface specifications and protocols

supports the SATA Revision 3.1 standard

supports SATA 6Gbps

Adaptive to SATA 3 Gbps and 1.5 Gbps

supports S.M.A.R.T features.

supports hot swapping

supports TRIM commands

compatibility

supports Windows 7/8.1/10

supports mainstream Linux operating systems

supports Kylin/UOS/Zhongke Fangde/Tianmai/Yihui/Ruihua and other operating systems.

Domestic operating system

Company Statement

This specification shall be subject to all YOTTAWIN handbooks or terms of use provided or made available to the customer. This specification is subject to change and/or update without prior notice.

The customer assumes sole and exclusive responsibility for compliance with safety, environmental, export, trade, and other applicable laws and regulations with respect to this specification. In addition, the customer shall assume sole and exclusive responsibility for any embedded or other use of the devices described in this specification in nuclear or ultra-hazardous applications, as well as in applications that could cause property damage, bodily injury, or death. All specifications are subject to change without prior notice.

Safety Instructions for Use

For the safety of users, please read and follow all instructions, warning signs, precautions, and notes in this manual before using and operating the equipment.

- Carefully read these safety instructions;
- Save this manual for long-term reference;
- Read the chapter detailing the operating environment of this device;

To prevent damage to the equipment caused by overvoltage, overcurrent, etc. during operation:

- Ensure the use of voltage and power settings;
- Ensure the correctness of the interface signal access level;

Do not attempt to repair the equipment.

In the following cases, the equipment must be repaired by authorized personnel:

- The equipment is immersed in liquid;
 - Being dropped, physically damaged or otherwise impaired;
 - Sustains obvious physical damage.
- 

catalogue

1 Brief Introduction.....	1
2 Size Of Product.....	2
2.1 capacity.....	2
2.2 service behavior.....	2
2.3 electrical character.....	3
2.4 ambient condition.....	3
2.5 reliability.....	4
2.6 Durability.....	4
3 Mechanical information.....	5
4 Pin and Signal Description.....	6
5 Product Principle Flowchart.....	8
6 Command and Command Set.....	9
7 Model.....	11
8 Install.....	11
8.1 power supply mode.....	11
8.2 Unboxing inspection and precautions.....	11
8.3 Installation and Preparation.....	11
9 Maintenance and Care.....	11
10 Precautions and Requirements.....	12
10.1 transport.....	12
10.2 keep in storage.....	12

1 Brief Introduction

M.2 interface SATA solid-state drive features high transfer speed, excellent reliability, strong shock resistance and low latency. The electronic disk adopts the SATA III interface protocol, uses the standard M.2 2280 form factor, and is equipped with high-performance NAND flash memory particles.

Main Functional Features

- Fully compatible with ATA/ATAPI-7 standards;
- Compatible with ATA/ATAPI-8 ACS4 mandatory commands;
- Supports local command queue (NCQ) command set;
- Supports dataset management commands;
- Supports end-to-end data protection;
- It adopts dynamic thermal protection technology and an intelligent overheating frequency reduction algorithm, which can automatically monitor and maintain a stable operating temperature. thereby further ensuring product performance.

2 Size Of Product

2.1 capacity

Table1 Capacity Correspondence

Physical Capacity	256GB	512GB	1TB	2TB
Available Capacity	238.47GB	476.94GB	953.87GB	1907.34GB

Note :

1. Due to the need to allocate part of the capacity for flash memory management and maintenance, the available capacity of SSDs will be smaller than their nominal capacity.

2.2 service behavior

Table2 Maximum Read and Write Performance

parameter	256GB	512GB	1TB	2TB	unit
Maximum sequential read performance of 1MB	556	556	555	561	MB/s
Maximum sequential write performance of 1MB	510	517	518	523	MB/s
Maximum random read performance of 4KB	36	44	58	72	KIOPS
Up to 4KB maximum random write performance	84	85	87	86	KIOPS

Note :

1. Performance data may deviate slightly due to differences in test tools and test environments.
2. 4KB =4096Bytes
3. 1Megabyte (MB) =1,000,000 Byte

Table3 IO response latency

Parameter	256GB	512GB	1TB	2TB	unit
4KB Read Latency(max)		130(Typ)			us
4KB Write Latency(max)		40(Typ)			us

Note :

1. The above latency measurements were obtained using sequential 4KB (4,096 bytes) IO operations with IOMeter configured at queue depth 1 and SSD write cache enabled. Variations in latency data may occur due to differences in testing tools and environments.

2.3 electrical character

Table4 Operating Voltage

Item	Range
Supply Voltage	3.3V±5%

Table5 Power Consumption

parameter	256GB	512GB	1TB	2TB	unit
Power consumption during write operation	2	2	2	2	W
idle power consumption	0.6	0.6	0.6	0.6	W

Note :

1. The operating power consumption is measured under the following conditions: 1 MB (1,048,576 bytes) IO operations, a queue depth of 1024, and sequential write operations on an empty SSD. The maximum average power consumption is collected from an external independent power supply during read operations.

2.4 ambient condition

Table6 Temperature

environmental parameter	Value	unit	Note
working Temperature	0 ~ +70	℃	
Storage Temperature	-40 ~ +85	℃	
Working humidity	5 ~ 90	%	
Storage humidity	90	%	non-coagulable

2.5 reliability

Table7 Reliability Specifications

Reliability parameter	Value	condition
UBER (Uncorrectable Bit Error Rate)	10^{-16}	/
MTBF (Mean Time Between Failures)	1.5 million hours	/
Data retention time after power outage	6 months	temperature $\leq 40^{\circ}\text{C}$

Note :

1. Refer to Table 1 in the JESD218 specification for UBER, FFR, and Workload values.

2.6 Durability

Table8 Tolerability specifications

Durability parameters	256GB	512GB	1TB	2TB	unit
TBW	75	150	300	600	TB
DWPD	0.16	0.16	0.16	0.16	times
Warranty period	3	3	3	3	year

Note :

1. The total write volume (TBW) and warranty period are determined by whichever comes first.
2. TBW: Total Written Data (Terabytes Written), the total amount of data written. (Refer to JESD219A specification for TBW write amplification testing value set at 3.5)

3 Mechanical information




Figure 1 Dimension reference diagram (unit: mm)

Table9 Dimension Specifications

specifications	Length (mm)	wide (mm)	Thickness (mm)
M.2 2280	80 ± 0.15	22 ± 0.15	2.15(MAX)

4 Pin and Signal Description



Figure2 SATA interface PIN pin diagram

Table10 M.2 SATA SSD interface definition

explain	type	pin	pin	type	explain
landing	GND	1	2	3.3 V	3.3 V
landing	GND	3	4	3.3 V	3.3 V
No internal electrical connection exists	NC	5	6	NC	No internal electrical connection exists
No internal electrical connection exists	NC	7	8	NC	No internal electrical connection exists
No internal electrical connection exists	NC	9	10	DAS/DSS	Device Activity/Disable Staggered Spin-up
No internal electrical connection exists	NC	11	12		Mechanical groove B
Mechanical groove B		13	14		Mechanical groove B
Mechanical groove B		15	16		Mechanical groove B
Mechanical groove B		17	18		Mechanical groove B
Mechanical groove B		19	20	NC	No internal electrical connection exists
landing	GND	21	22	NC	No internal electrical connection exists
No internal electrical connection exists	NC	23	24	NC	No internal electrical connection exists
No internal electrical connection exists	NC	25	26	NC	No internal electrical connection exists
landing	GND	27	28	NC	No internal electrical connection exists
No internal electrical connection exists	NC	29	30	NC	No internal electrical connection exists
No internal electrical connection exists	NC	31	32	NC	No internal electrical connection exists
landing	GND	33	34	NC	No internal electrical connection exists

No internal electrical connection exists	NC	35	36	NC	No internal electrical connection exists
No internal electrical connection exists	NC	37	38	DEVSLP	If the device sleep input exceeds the threshold, the host will notify the SSD to enter a low-power state.
landing	GND	39	40	NC	No internal electrical connection exists
Receive HOST-side RX differential signal	SATA-RX+	41	42	NC	No internal electrical connection exists
Receive HOST-side RX differential signal	SATA-RX-	43	44	NC	No internal electrical connection exists
landing	GND	45	46	NC	No internal electrical connection exists
Receive the HOST-side TX differential signal	SATA-TX-	47	48	NC	No internal electrical connection exists
Receive the HOST-side TX differential signal	SATA-TX+	49	50	NC	No internal electrical connection exists
landing	GND	51	52	NC	No internal electrical connection exists
No internal electrical connection exists	NC	53	54	NC	No internal electrical connection exists
No internal electrical connection exists	NC	55	56	NC	No internal electrical connections are default (URATTX optional)
landing	GND	57	58	NC	No internal electrical connections are default (URATRX optional)
Mechanical groove M		59	60		Mechanical groove M
Mechanical groove M		61	62		Mechanical groove M
Mechanical groove M		63	64		Mechanical groove M
Mechanical groove M		65	66		Mechanical groove M
No internal electrical connection exists	NC	67	68	NC	No internal electrical connection exists
landing	GND	69	70	3.3 V	3.3V Power

landing	GND	71	72	3.3 V	3.3V Power
landing	GND	73	74	3.3 V	3.3V Power
landing	GND	75			

5 Product Principle Flowchart

The primary function of an M.2 SATA solid-state drive is to fulfill users' data storage and retrieval requirements. The main controller communicates with the host port via the SATA III interface, parsing valid data through the SATA III protocol and link verification before distributing it to the flash memory chip array for storage management. The internal architecture of an M.2 SATA SSD is illustrated in the diagram below.




Figure 3 Block diagram of SSD control board product principle

6 Command and Command Set

Table11 Supported ATA command list

command name	Command code (hexadecimal)	command name	Command code (hexadecimal)
CHECK POWER MODE	E5h / 98h	DEVICE CONFIGURATION	B1h
DOWNLOAD MICROCODE	92h	DOWNLOAD MICROCODE DMA	93h
EXECUTE DEVICE DIAGNOSTIC	90h	FLUSH CACHE	E7h
FLUSH CACHE EXT	EAh	IDENTIFY DEVICE	ECh
IDLE	E3h / 97h	IDLE IMMEDIATE	E1h / 95h
INITIALIZE DEVICE PARAMETERS	91h	READ BUFFER E	4h
READ BUFFER DMA	E9h	READ DMA	C8h
READ DMA (w/o retry)	C9h	READ DMA EXT	25h
READ FPDMA QUEUED	60h	READ LOG DMA EXT	47h
READ LOG EXT	2Fh	READ MULTIPLE	C4h
READ MULTIPLE EXT	29h	READ NATIVE MAX ADDRESS	F8h
READ NATIVE MAX ADDRESS EXT	27h	READ SECTORS	20h
READ SECTORS (w/o retry)	21h	READ SECTORS EXT	24h
READ VERIFY SECTORS	40h	READ VERIFY SECTORS (w/o retry)	41h
READ VERIFY SECTORS EXT	42h	RECALIBRATE	10h
NCQ NONDATA	63h	SANITIZE DEVICE	B4h
SECURITY DISABLE PASSWORD	F6h	SECURITY ERASE PREPARE	F3h
SECURITY ERASE UNIT	F4h	SECURITY FREEZE LOCK	F5h

command name	Command code (hexadecimal)	command name	Command code (hexadecimal)
SECURITY SET PASSWORD	F1h	SECURITY UNLOCK	F2h
SEND FPDMA QUEUED	64h	SET DATE N TIME	77h
SET FEATURES	EFh	SET MAX ADDRESS	F9h
SET MAX ADDRESS EXT	37h	SET MULTIPLE MODE	C6h
SLEEP	E6h / 99h	S.M.A.R.T.	B0h
STANDBY	E2h / 96h	STANDBY IMMEDIATE	E0h / 94h
TRIM	06h	WRITE BUFFER	E8h
WRITE BUFFER DMA	EBh	WRITE DMA	CAh
WRITE DMA (w/o retry)	CBh	WRITE DMA EXT	35h
WRITE DMA FUA EXT	3Dh	WRITE FPDMA QUEUED	61h
WRITE LOG DMA EXT	57h	WRITE LOG EXT	3Fh
WRITE MULTIPLE	C5h	WRITE MULTIPLE EXT	39h
WRITE MULTIPLE FUA EXT	CEh	WRITE SECTORS	30h
WRITE SECTORS (w/o retry)	31h	WRITE SECTORS EXT	34h
WRITE UNCORRECTABLE EXT	45h		

7 Model

Table12 Product Model Table without Secure Erase

Product Parameter	model	capacity
M.2 SATA	HESAM8256G55-NEQ3WB	256GB
	HESAM8512G55- NEQ3WB	512GB
	HESAM8001T55- NEQ3WB	1TB
	HESAM8002T55- NEQ3WB	2TB

8 Install

8.1 power supply mode

The operating voltage of the SSD control board is DC (3.3±5%) V.

8.2 Unboxing inspection and precautions

- Before opening the box, inspect whether the product packaging is intact and check for any signs of compression or damage.
- After implementing static electricity protection measures, the anti-static bag may be opened to remove the product. Upon removal, visually inspect the product's appearance to ensure it remains intact.

8.3 Installation and Preparation

- After implementing electrostatic protection measures, remove the product from the electrostatic protective bag.
- Check if the environment is functioning properly;
- Check whether the signal and power connectors are functioning properly.

9 Maintenance and Care

Maintenance and servicing of the SSD control board shall be conducted every two years, and the SSD must be powered off during maintenance. Maintenance contents include:

- Inspect for physical integrity; wipe the connector with alcohol.
- Check for any looseness in connectors and fasteners. If loosening is detected, reinforce them promptly.

10 Precautions and Requirements

10.1 transport

- a) Packaged products can be transported by conventional means of transportation. During transportation, appropriate measures should be taken to protect against rain and snow.
- b) Concomitant transportation with corrosive substances such as acids and alkalis is prohibited;
- c) Do not stack heavy objects on top of products;
- d) Handle with care during transportation.

10.2 keep in storage

The product is recommended to be stored in a dedicated warehouse with a Temperature range of 0°C to 35°C, relative humidity not exceeding 80%, and free from strong magnetic fields. The product must not be stored together with acids, alkalis, or corrosive substances.